


U
1006-45°

**SEAMLESS
MANUAL
EDGE BANDING
SOLUTION**




**SMART SOLUTION
FOR ENHANCE QUALITY**

U1006-45°




Ø 525 mm

Coil Holding
Capacity




Max. 3 mm

Pneumatic Cutter



Gluing



Max. 3 mm

Wooden Strip

U1006-45°

A large variety of construction and performance manual edgebanding machine models are available from Umaboy.

Salient Features

- ▶ Variable feed speed of edge banding.
- ▶ Alluminium glue pot with covering heat insulation material.
- ▶ Foot and micro cutting system for edge cutting.
- ▶ High speed motor equipped with ' V ' groove tool
- ▶ 45° & Straight pressing unit
- ▶ The top workstation is equipped with Hylam sheet.

U1006-45°

Technical Specification

Model	U1006-45°
Maximum thickness of work piece	10 to 50 mm
Tape thickness	0.4 to 2 mm
Glue pot capacity	2 kgs. approx
Heating element	3 kw
Tape cutting mechanism	Pneumatic
Control of tape cutting	Micro/Foot Switch
Working speed per minute	0 to 10 mts (Variable)
Motor	1 HP
Air Pressure	5 to 7 kg/cm ²
Tape coil dia	525 mm

Machine Specification



CONTROL PANEL

- ▶ Equipped with Length counter meter for processing pre define length of panel makes easy to operate the machine.
- ▶ Temperature controller is displaying of glue pot temprature
- ▶ glue roller speed can be adjust according to the users by ariable speed pot.
- ▶ Micro transfer / Foot transfer each alternative are to be had for running in this machine. (Call upon a users)
- ▶ 45° degree band grooving can be manage by Micro swith / Foor swith (call upon User)
- ▶ - Result can't be meet as in line with expectation.



GLUE POT

- ▶ Equipped with 2.5 kg capacity of glue pot.
- ▶ For Increase and decrease Glue temprature at the glue roller is can be manage through nobe.
- ▶ Alluminium Diy casted glue pot offers an appropriate and uniform performance in every day working.




SCISSOR UNIT

- ▶ Scissor Functionality is Pneumatically Equipped with SS sharp blade to cut edge band smoothly.
- ▶ It's Connected to Foot Switch and Micro Switch (Call upon user)

MANUAL EDGE BANDER


U1006-45°

Machine Specification



45° TILTING TABLE

- ▶ Extended Swivel bar is to be had for working in a big length of panel.
- ▶ Tilting desk is Equipped to apply edgeband on panel with 45° angle.
- ▶ It can be move till 45° and help to hold panel with perfect position and get better stability.
- ▶ The top workstation is equipped with Hylam sheet, which accomplished with Heat resistant, shock proof, water proof.



45° PVC EDGE BAND PRESSING UNIT

- ▶ Equipped with 45° roller to pressing band for perfect stuck on panel to long lasting performance.
- ▶ This rollers are one after the other symmetrically and with static position pressing edge band to straight and at 45° to make strong stuckness.



45° PVC V GROOVE UNIT

- ▶ 45° PVC V groove is functioning to make groove on edge band in order that band can be stuck with panel in duck beak shape.
- ▶ High speed motor is equipped to V groove on band.





WOODWORKING MACHINERY
MANUFACTURING

We would love to
hear from you!

CONTACT US

HEADQUARTER

3/c. shiv estate, opp. radhika society,
near baroda expressway, NH-8,
Ahmedabad - 382 445

CONTACT NUMBER

+91-99255 19009

+91-96620 29892